

R2 Series High Efficiency Heat Recovery (106-112kW)



The **City Multi R2 Series High Efficiency Heat Recovery** system delivers exceptional seasonal energy performance, providing simultaneous heating and cooling while redistributing surplus heat where it's needed. This advanced heat recovery approach can achieve up to 30% energy savings over conventional systems.

As the only 2-pipe heat recovery solution on the market, the modular City Multi R2 Series simplifies installation and maintenance while offering complete design flexibility for applications such as hotels, offices, and leisure spaces.



Key Features & Benefits:

- **Heat Recovery Operation** - Delivers up to 30% energy savings compared to heat pump systems through advanced heat recovery
- **Lower GWP R32 Refrigerant** - for reduced carbon impact and future-ready legislation compliance
- **Simultaneous Heating & Cooling** - Meets diverse comfort needs across different zones at the same time for optimal occupant satisfaction
- **Unique 2-Pipe System** - Simplifies installation and maintenance while reducing system complexity
- **Ultra-Compact Modular Design** - Smaller unit footprint allows installation in tight spaces without compromising on performance
- **Broad Indoor Unit Compatibility** - Connects to a wide range of unit types and capacities, making it suitable for varied building applications
- **Patented Vertical Flat Tube Heat Exchanger** - Maximises heat exchange efficiency, reducing energy consumption and run costs
- **Reduced Refrigerant Charge** - Uses less refrigerant than the YXM standard efficiency model, lowering embodied carbon and whole-life carbon impact
- **Extended Heating Range (-25°C)** - Ensures reliable heating even in severe winter conditions by maintaining efficient system operation
- **Easy-to-Maintain Safety Feature Options** - For reduced onsite time and costs while supporting occupant peace of mind
- **Enhanced Defrost Technology** - Reduces system downtime during defrost cycles, minimising temperature fluctuations and maintaining reliable indoor heating for consistent occupant comfort
- **Low Noise Operation** - Features a 5-step low noise mode that minimises sound levels for quieter surroundings
- **113m Vertical Height Separation** - Offers generous height allowance between indoor and outdoor units, enabling design flexibility in larger buildings




R32



PURY-EM-YSXM-A OUTDOOR UNITS		PURY-EM950YSXM-A	PURY-EM1000YSXM-A
CAPACITY (kW)	Heating (nominal max)	114.0	116.0
	Cooling (nominal)	106.0	112.0
	High Performance Heating (UK)	106.0	107.9
	COP Priority Heating (UK)	100.3	102.1
	Cooling (UK)	94.3	99.7
POWER INPUT (kW)	Heating (nominal max)	34.65	35.58
	Cooling (nominal)	33.22	35.89
	High Performance Heating (UK)	40.54	41.63
	COP Priority Heating (UK)	36.73	37.71
	Cooling (UK)	30.56	33.02
COP / EER (nominal max)		3.29 / 3.19	3.26 / 3.12
SCOP / SEER		4.40 / 7.44	4.35 / 7.20
MAX NO. OF CONNECTABLE INDOOR UNITS		50	50
MAX CONNECTABLE CAPACITY		50~150% OU Capacity	50~150% OU Capacity
AIRFLOW (m³/min)	High	315 / 315	315 / 315
	Gas	41.28 (1-5/8")	41.28 (1-5/8")
PIPE SIZE mm (in)	Liquid	28.58 (1-1/8")	28.58 (1-1/8")
	Heating / Cooling	72.0 / 69.0	72.0 / 71.0
SOUND PRESSURE LEVEL (dBA) @ 1m		94.0 / 89.0	95.0 / 91.0
SOUND POWER LEVEL (dBA) @ 100% Capacity		90.5 / 87.5	91.0 / 88.0
SOUND POWER LEVEL (dBA) @ 90% Capacity		86.5 / 83.5	87.0 / 84.0
SOUND POWER LEVEL (dBA) @ 75% Capacity		317 + 317	317 + 317
WEIGHT (kg)		1207 + 1207	1207 + 1207
DIMENSIONS (mm)		740	740
(1798mm without legs)		1858	1858
ELECTRICAL SUPPLY ^{*1}		380-415v, 50Hz	380-415v, 50Hz
PHASE ^{*1}		Three	Three
STARTING CURRENT (A) ^{*1}		8	8
NOMINAL SYSTEM RUNNING CURRENT (A) ^{*1}		Heating / Cooling [MAX]	55.5 / 53.2 [30.2 + 33.3]
GUARANTEED OPERATING RANGE (°C)		Heating / Cooling	-25~-15.5 / -5~-52
FUSE RATING (MCB sizes BS EN 60947-2) - (A) ^{*1}			1 x 32 / 1 x 40
MAINS CABLE No. Cores ^{*1}			4 + earth / 4 + earth
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R32 (GWP 675)			12.6 / 8.5
MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R32 (GWP 675)			52.5 / 35.6

Notes: ErP Lot 6 calculation method to EN14825. *1 A separate power supply is required for each module. Where more than one figure is quoted there are multiple modules.

PURY-EM950/1000YSXM-A DIMENSIONS



Telephone: +353 1 419 8800
email: sales.info@meir.mee.com
les.mitsubishielectric.ie



IRELAND Mitsubishi Electric Europe, Plunkett House, Grange Castle Business Park, Nangor Road, Dublin 22, D22 YRK4 Ireland. Telephone: (00353) 1 4198800 Email: sales.info@meir.mee.com
Web: les.mitsubishielectric.ie

UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division, Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England. Telephone: 01707 282880

Country of origin: United Kingdom - Italy - Turkey - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2025. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only and please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP:2088), R32 (GWP:675), R407C (GWP:1774), R134a (GWP:1430), R513A (GWP:631), R454B (GWP:466), R515B (GWP:292), R454C (GWP:148), R1234ze (GWP:7) or R1234yf (GWP:4). *These GWP values are based on Regulation (EU) No 517/2014 from IPCC 4th edition. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a hydrocarbon, R290 (GWP:0.02). *These GWP values are based on IPCC 6th edition.

Effective as of August 2026

